I, Yvette SUEUR

of CABINET SUEUR & L'HELGOUALCH 109, boulevard Haussmann F-75008 - PARIS (France)

do hereby certify that I am knowledgeable in the French language in which International Patent Application PCT/FR03/02104 was filed, and that, to the best of my knowledge and belief, the English translation is a true and complete translation of the above identified international application as filed.

Signature of Translator:

Dated this 18th day of January 2005.

Organophosphorus compounds comprising a polysulfide bridge

The present invention relates to organophosphorus compounds comprising a polysulfide bridge, to their process of preparation and to their use as coupling agent between an inorganic filler or a metal filler and an elastomer.

known to use coupling agents processes 10 is in targeted at reinforcing polymer matrices by inorganic particles. Mention may in particular be made of the corresponding the to silanes $(RO)_3Si(CH_2)_nS_m(CH_2)_nSi(OR_3)$ in which R = Et or Me, n = 2or 3, m = 2 or 4 (DE 2141159), or in which R = Et, 15 n = 2 or 3, m = 2 or 4 (DE 3311340), or in which R = Et, n = 3, m = 4 (DE 10015308). The improvement in the mechanical properties originates from the increase in the adhesion between the polymer matrix and the 20 inorganic filler. These coupling agents of the silane type are particularly effective when the inorganic particles are silica or clays. However, the improvement in the mechanical properties of the matrix is smaller the inorganic filler comprises, for example, titanium oxide or calcium carbonate and the adhesion 25 with metal surfaces is poor.

In addition, it is known that the use of compounds of the phosphate, phosphonate or phosphinate type, as a replacement for compounds of the organosilane type, makes possible good adhesion of the phosphate compound to inorganic materials, such as metal oxides or metal surfaces. For example, G. Guerrero et al. [(2001), J. Mater. Chem, 11(12), 3161-3165] describes the grafting of phenylphosphonic acid or its ethyl or trimethylsilyl esters to alumina. G. Guerrero et al. [(2001), Chem. 13, 4367-4373] describes the grafting phenylphosphonic acid or phenylphosphinic acid or their ethyl or trimethylsilyl esters to TiO2. The formation

30

35

of phosphonic acid monolayers on metal surfaces made of copper or brass is described aluminum, 15, J.G. Alsten [Langmuir, (1999) 7605-7614]. Nakatsuka [Polym. Prep., Am. Chem. Soc., Div. Polym. Chem., (1983) 24(1), 202-203] describes the grafting of various phosphates, in particular (HO)₂P(O)-OC₈H₁₇, to CaCO3. The use of an additive of the mercaptoalkylelastomer compositions type in phosphonate comprise silica is described in US-4 386 185; the additive is a phosphonate (RO)₂P(O)-(CR'₂)_nSH, R being 10 an alkyl, a cycloalkyl or an arylalkyl, R' being H or alkyl and n being 1 to 8. The preparation of phosphorus compounds used as catalysts is disclosed in EP-1 157 994; the compounds correspond to the formula $(MO)_{m}P(O)(OX)_{n}(R)_{p}[-(O)_{x}-(Z-A)]_{q}$ in which 15 R = hydrocarbon,m+n+p+x = 3,monovalent cation, X = hydrocarbon or trialkylsilane and A can comprise sulfur originating, for example, from a thiol or an SO3 group.

20

25

It is known that the use of compounds of the monoalkoxytitanate type as coupling agent makes it possible to increase the amount of inorganic filler added to a thermoplastic material, without harming its fluidity (S. Monte et al., (1976) Proc., Annu. Conf., Reinf. Plast./Compos. Inst., Soc. Plast. Ind., 31, 6-E).

the tetrasodium 2,2'-Furthermore, compounds of 30 (dithiobis) ethanephosphonate type, of use as (WO 98/14426), and dithioethers of the medicament $(HO)_{2}P(O) - (CH_{2})_{m}S_{2} - (CH_{2})_{m} - P(O)(OH)_{2}$ type, of use reducing the toxic effect of carboplatin (WO 98/11898), use of known. Ιn addition, the disulfides comprising terminal groups of the ethylphosphonate 35 as additive in the lubrication of fuels type, (GB 1 189 304), is known.

The aim of the present invention is to provide

compounds of use as coupling agents between a polymer matrix and an inorganic or metal filler which exhibit improved properties, in particular with inorganic fillers other than silicas.

5

A subject matter of the present invention is compounds which correspond to the formula:

$$(RO)_{2-t}R^{1}_{t}P(O) - O_{x} - (CH_{z})_{y} - S_{z} - (CH_{2})_{y} - O_{x} - P(O)(OR)_{2-t}R^{1}_{2}$$
(I)

10

in which:

- R represents a hydrogen, an alkyl, an aryl, a trialkylsilyl, a trialkylamino or an alkali metal;
- R¹ represents an alkyl or an aryl;
- 15 x is 0 or 1;
 - y is an integer from 1 to 22, preferably from 2 to 4;
 - $z \geq 3$;
 - t is 0 or 1.

20

In the compounds of the invention, when R is an alkyl group, it is preferably chosen from alkyl radicals having from 1 to 6 carbon atoms. When R is an aryl group, it is preferably chosen from phenyl, benzyl and tolyl. The trialkylsilyl group is preferably an R'3Sigroup in which the R' substituents represent identical or different alkyl groups having from 1 to 3 carbon atoms. The trialkylamino group is preferably an R"3N-group in which the R" substituents represent identical or different alkyl groups having from 1 to 5 carbon atoms. When R is an alkali metal, preference is given in particular to Na and K.

The R¹ substituent is preferably an alkyl radical having from 1 to 18 carbon atoms or an aryl radical chosen from phenyl, benzyl and tolyl.

It is possible to single out, among the compounds of the invention, the compounds for which x=0, that is

to say the phosphonates $(RO)_2P(O)-(CH_2)_y-S_z-(CH_2)_y-P(O)_2(OR)_2 \qquad (II) \qquad \text{and} \qquad the phosphinates} \quad (RO)_2P(O)-(CH_2)_y-S_z-(CH_2)_y-P(O)_2(OR)_2 \qquad (IV)_z .$

- In addition, mention may be made of the compounds in which x = 1, that is to say the phosphates $(RO)_2 P(O) O (CH_2)_y S_z (CH_2)_y O P(O) (OR)_2 (III) \text{ and } (RO)_R^1 P(O) O (CH_2)_y S_z (CH_2)_y O P(O) (OR)_R^1 (V) .$
- 10 Preference is very particularly given, among these compounds, to those which have a mean number of sulfur atoms z of between 3 and 5 and more particularly the compounds in which z is on average equal to 4.
- 15 The compounds according to the invention can be prepared by processes employing conventional reactions of sulfur and phosphorus chemistry. A few specific cases are indicated below.
- The phosphonate compounds corresponding to the formula (II) in which z=4 and R is an alkyl Ra can be prepared, for example, by the following process:
 - during a first stage, the trialkyl phosphite $P(ORa)_3$ (VI) is reacted with the dibromoalkylene
- 25 Br- $(CH_2)_y$ -Br (VII) at a temperature of the order of $140^{\circ}C$ in order to obtain Br- $(CH_2)_y$ -P(O)(ORa)₂ (VIII),
 - during a second stage, the phosphonate $Br-(CH_2)_y-P(O)$ (ORa)₂ (VIII) is reacted with Na_2S_4 under reflux of the methanol. A product is obtained having a mean composition corresponding to the formula

 $(RaO)_2P(O)-(CH_2)_y-S_4-(CH_2)_y-P(O)\;(ORa)_2 \qquad (IIa in which Ra is an alkyl.$

30

A phosphinate (IVa) corresponding to the formula (IV) in which R is Ra and z=4 can be obtained by a similar process, the reactant $P(ORa)_3$ (VI) being replaced during the first stage by a reactant $P(ORa)_2R^1$ (IX).

A phosphonate which corresponds to the formula (II) in

which z=4 and R is a trialkylsilyl R' $_3$ Si can be obtained by reacting the compound (IIa) with a trialkylsilyl bromide R' $_3$ SiBr according to the following reaction scheme:

5

$$(RaO)_{2}P(O) - (CH_{2})_{y} - S_{4} - (CH_{2})_{y} - P(O) (ORa)_{2} + 4R'_{3}Si \rightarrow (R'_{3}SiO)_{2}P(O) - (CH_{2})_{y} - S_{4} - (CH_{2})_{y} - P(O) (OSiR')_{2}$$
 (IIb)

A compound $(HO)_2P(O)-(CH_2)_y-S_4-(CH_2)_y-P(O)$ $(OH)_2$ (IIc) which corresponds to the formula (II) in which z=4 and R is H can be obtained either by hydrolysis of the corresponding compound (IIa) or by hydrolysis or by alcoholysis of the corresponding compound (IIb). The hydrolysis of the compound (IIb) is a mild method which is particularly preferred.

A phosphate (IIIa) corresponding to the mean formula (III) in which R is H can be obtained by a process in which:

- 20 during a first stage, $P(0)Cl_3$ is reacted with a compound $HO(CH_2)_yCl$ in stoichiometric proportions in order to obtain the compound $Cl(CH_2)_yOP(0)Cl_2$;
 - during a second stage, the compound $Cl(CH_2)_yOP(0)Cl_2$ is hydrolyzed in order to obtain the compound $Cl(CH_2)_yOPO_3H_2$;
 - during a third stage, $Cl(CH_2)_yOPO_3H_2$ is reacted with Na_2S_4 under reflux of the methanol and then an ion exchange is carried out in order to obtain the compound $(HO)_2P(O)-O-(CH_2)_y-S_z-(CH_2)_y-O-P(O)(OH)_2$.

30

25

The reaction scheme corresponding to this process is as follows:

$$P(O)Cl_3 + HO(CH_2)_yCl \rightarrow Cl(CH_2)_yOP(O)Cl_2 + HCl$$

$$Cl(CH_2)_yOP(O)Cl_2 + 2 H_2O \rightarrow Cl(CH_2)_yOPO_3H_2 + 2 HCl$$

$$1) MeOH, reflux$$

35

2 CI(CH₂)_yOPO₃H₂ + Na₂S₄
$$\rightarrow$$
 H₂O₃PO(CH₂)_y-S₄-(CH₂)_yOPO₃H₂ + 2 NaCl 2) ion exchange

The organophosphorus compounds of the present invention

be used as coupling agents between inorganic fillers and elastomers in the technical fields in which fillers are used to improve the properties elastomers. Although the compounds in which R is a trialkylsilyl are sensitive to hydrolysis, they can nevertheless be used as coupling agents. Mention may in particular be made, among inorganic fillers, of oxides, and carbonates, such as, for hydroxides example, silica, alumina, titanium oxide, silicoaluminates and clays. Mention may also be made of metallic materials, such as steels, copper and aluminum.

The present invention is described in more detail by the examples which are given below by way of 15 illustration but to which it is not, however, limited.

Example 1

Preparation of $(EtO)_2P(O) - (CH_2)_3 - S_4 - (CH_2)_3 - P(O)(OEt)_2$

20

25

30

35

10

During a first stage, diethyl 3-bromopropylphosphonate $(EtO)_2P(O)-(CH_2)_3$ -Br was prepared in the following way. One equivalent of triethyl phosphite $P(OEt)_3$ and 1.5 equivalents of 1,3-dibromopropane were introduced into a reactor under a nitrogen atmosphere. The reactor was brought to $140^{\circ}C$ and was maintained at this temperature with stirring for 15 hours. After distillation, the compound $(EtO)_2P(O)-(CH_2)_3$ -Br was obtained with a yield of 60% with respect to the triethyl phosphite introduced.

Subsequently, 1.71 g of Na₂S₄ and 20 ml of anhydrous introduced into were reactor a nitrogen atmosphere. The reactor was heated to reflux (2 equivalents) of the methanol and 5 a $(EtO)_2P(O)-(CH_2)_3-Br$, dissolved in 20 ml of anhydrous methanol, were added dropwise. After refluxing for half an hour, the reactor was cooled to ambient temperature. After separation of the NaBr precipitate, evaporation under vacuum and filtration, 30 ml of anhydrous toluene were added. After filtration and evaporation under vacuum, 3.7 g of a yellow oil were obtained. The formation of $(EtO)_2P(O)-(CH_2)_3-S_4-(CH_2)_3-P(O)(OEt)_2$ with a yield of 76% is confirmed by proton NMR and by elemental analysis.

Example 2

10 Preparation of $(Me_3SiO)_2P(O) - (CH_2)_3 - S_4 - (CH_2)_3 - P(O) (OSiMe_3)_2$

5 g of $(EtO)_2P(O)-(CH_2)_3-S_4-(CH_2)_3-P(O)$ (OEt)₂ (obtained according to the process of example 1) in 20 ml of dichloromethane were introduced into a reactor under a nitrogen atmosphere. 8 g of Me₃SiBr were added and the reaction mixture was stirred at ambient temperature for 10 hours. After evaporation under vacuum, 6.6 g of a yellow oil were obtained. Proton NMR and elemental analysis confirm the formation of $(Me_3SiO)_2P(O)-(CH_2)_3-S_4-(CH_2)_3-P(O)$ (OSiMe₃)₂.

Example 3

Preparation of $(HO)_2P(O) - (CH_2)_3 - S_4 - (CH_2)_3 - P(O)(OH)_2$

25

30

15

20

5

compound $(Me_3SiO)_2P(O) - (CH_2)_3 - S_4 - (CH_2)_3$ the P(O) (OSiMe₃)₂ obtained according to the process example 2 were introduced into a reactor and 30 ml of methanol were added. After stirring at 40°C for 6 hours and evaporation under vacuum, 2.9 g of a yellow solid were obtained. Proton NMR elemental analysis and confirm the formation of $(HO)_2P(O) - (CH_2)_3 - S_4 - (CH_2)_3 P(O)(OH)_2$.